

SECTION 1: IDENTIFICATION

DISTRIBUTED BY:	YOUNG INNOVATIONS, INC. - DBA [ORTHOSTORE]
ADDRESS:	2260 WENDT STREET
CITY, STATE, ZIP:	ALGONQUIN, IL 60102 USA
TELEPHONE:	1-800-275-0020
PRODUCT ITEM NO.:	105-25
PRODUCT NAME/IDENTIFIER:	ARCH WIRE - MULTI STRAND SS
COMMON NAME:	STAINLESS STEEL
RECOMMENDED USE OF THE CHEMICAL & RESTRICTIONS ON USE:	N/A
24 HR EMERGENCY PHONE #	INFOTRAC 1-800-535-5053 / OUTSIDE U.S. 1-352-323-3500

SECTION 2: HAZARD(S) IDENTIFICATION

SOLID METALLIC PRODUCTS ARE GENERALLY CLASSIFIED AS "ARTICLES" AND DO NOT CONSTITUTE A HAZARDOUS MATERIAL IN THEIR SOLID FORM. DURING PROCESSING, DUSTS AND FUMES GENERATED HAVE THE FOLLOWING HAZARDS:

CLASSIFICATION:

PHYSICAL	HEALTH
NON-HAZARDOUS	SKIN SENSITIZER CATEGORY 1 CARCINOGEN CATEGORY 1B SPECIFIC TARGET ORGAN TOXICITY – REPEAT EXPOSURE CATEGORY 1 (LUNGS, BRAIN, AND CNS) TOXIC TO REPRODUCTION CATEGORY 2 RESPIRATORY SENSITIZER CATEGORY 1B

HAZARDS NOT OTHERWISE CLASSIFIED: NONE

SYMBOL(S)



SIGNAL WORD

DANGER!

PRECAUTIONARY STATEMENT(S)

HAZARD STATEMENT(S)	PREVENTION
<ul style="list-style-type: none"> MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED. MAY CAUSE AN ALLERGIC SKIN REACTION MAY CAUSE CANCER. CAUSES DAMAGE TO LUNGS, BRAIN AND CNS THROUGH PROLONGED OR REPEATED EXPOSURE. SUSPECTED OF DAMAGING MALE FERTILITY. 	<ul style="list-style-type: none"> OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. DO NOT BREATHE DUST, OR FUME. IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION. WASH THOROUGHLY AFTER HANDLING. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. CONTAMINATED WORK CLOTHING MUST NOT BE ALLOWED OUT OF THE WORKPLACE. WEAR PROTECTIVE GLOVES.
STORAGE	
<ul style="list-style-type: none"> STORE LOCKED UP. 	

SECTION 2: HAZARD(S) IDENTIFICATION (CONT.)

PRECAUTIONARY STATEMENT(S) (CONT.)

DISPOSAL	RESPONSE
<ul style="list-style-type: none"> DISPOSE OF CONTENTS AND CONTAINER IN ACCORDANCE WITH LOCAL AND NATIONAL REGULATIONS. 	<ul style="list-style-type: none"> IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER. IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ATTENTION. IF EXPOSED OR CONCERNED: GET MEDICAL ATTENTION. WASH CONTAMINATED CLOTHING BEFORE REUSE. IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. IF EXPERIENCING RESPIRATORY SYMPTOMS: CALL A POISON CENTER OR DOCTOR.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NO.	WEIGHT %
CHROMIUM	7440-47-3	10-<25
NICKEL	7440-02-0	1-<10
MANGANESE	7439-96-5	0.1-<2.5
COBALT	7440-48-4	0.1-<1%

THE SPECIFIC IDENTITY AND/OR EXACT PERCENTAGE HAVE BEEN WITHHELD AS A TRADE SECRET.

SECTION 4: FIRST AID MEASURES

INGESTION: IF DUST IS SWALLOWED, SEEK MEDICAL ATTENTION.

INHALATION: IF OVEREXPOSED TO DUST OR FUMES REMOVE VICTIM TO FRESH AIR. IF EXPERIENCING RESPIRATORY SYMPTOMS GET IMMEDIATE MEDICAL ATTENTION.

EYE CONTACT: FLUSH EYES THOROUGHLY WITH WATER, HOLDING OPEN EYELIDS. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

SKIN CONTACT: WASH EXPOSED SKIN WITH SOAP AND WATER. IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ATTENTION. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED: EYE AND SKIN CONTACT WITH DUST MAY CAUSE MECHANICAL IRRITATION. MAY CAUSE GASTROINTESTINAL EFFECTS IF SWALLOWED. SUSPECTED OF DAMAGING MALE FERTILITY. CAUSES DAMAGE TO BRAIN AND CNS THROUGH PROLONGED OR REPEATED EXPOSURE. EXCESSIVE EXPOSURE TO WELDING FUMES, GASES OR DUST MAY CAUSE IRRITATION OF EYES, NOSE OR THROAT. INHALATION OF DUSTS OR FUMES MAY CAUSE AN ALLERGIC RESPIRATORY RESPONSE. INHALATION OF FUMES MAY RESULT IN METAL FUME FEVER (METALLIC TASTE IN MOUTH, DRYNESS AND IRRITATION OF THROAT, CHILLS AND FEVER). CAUSES DAMAGE TO LUNGS THROUGH PROLONGED OR REPEATED INHALATION. MAY CAUSE AN ALLERGIC SKIN REACTION. MAY CAUSE CANCER.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT, IF NECESSARY: IMMEDIATE MEDICAL ATTENTION IS REQUIRED FOR ALLERGIC RESPIRATORY RESPONSE.

SECTION 5: FIRE FIGHTING MEASURES

SUITABLE (AND UNSUITABLE) EXTINGUISHING MEDIA: NON-FLAMMABLE. WILL NOT SUPPORT COMBUSTION. USE ANY MEDIA THAT IS APPROPRIATE FOR THE SURROUNDING FIRE. DO NOT USE WATER ON MOLTEN METAL.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL: AT TEMPERATURES ABOVE THE MELTING POINT, HAZARDOUS FUMES CONTAINING METAL OXIDES AND OTHER ALLOYING ELEMENTS MAY BE PRODUCED.

SECTION 5: FIRE FIGHTING MEASURES(CONT.)

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: FIREFIGHTERS SHOULD WEAR FULL EMERGENCY EQUIPMENT AND NIOSH APPROVED POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS FOR ALL FIRES INVOLVING CHEMICAL PRODUCTS.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: WEAR APPROPRIATE PROTECTIVE CLOTHING AND EQUIPMENT (SEE SECTION 8). AVOID CONTACT WITH SKIN, EYES OR CLOTHING. DO NOT BREATHE DUST OR FUME.
SDS FORM 002 PAGE 3 OF 6 ISSUE DATE: 11-10-21

ENVIRONMENTAL PRECAUTIONS: AVOID RELEASE INTO THE ENVIRONMENTAL. REPORT RELEASES AS REQUIRED BY LOCAL, STATE AND FEDERAL AUTHORITIES.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: PICK UP MATERIAL AND PLACE INTO A CONTAINER FOR DISPOSAL OR REPROCESSING. IF DUST IS PRESENT, WET DOWN AND COLLECT IN A MANNER TO MINIMIZE THE GENERATION OF AIRBORNE DUSTS OR VACUUM WITH A HIGH EFFICIENCY VACUUM CLEANER. AVOID DISPERSAL OF DUST IN THE AIR (I.E., CLEARING DUST SURFACES WITH COMPRESSED AIR.).

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: NOT APPLICABLE TO STAINLESS STEEL IN SOLID STATE. FOR DUSTS OR FUMES CREATED DURING PROCESSING USE THE FOLLOWING PRECAUTIONS: AVOID CONTACT WITH EYES, SKIN AND CLOTHING. AVOID CREATING AND BREATHING DUSTS. WEAR PROTECTIVE CLOTHING AND EQUIPMENT AS DESCRIBED IN SECTION 8. USE ONLY WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS MATERIAL. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: NO SPECIAL STORAGE CONDITIONS FOR STAINLESS STEEL IN SOLID STATE. STORE AWAY FROM ACIDS AND INCOMPATIBLE MATERIALS.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

CHEMICAL NAME	ACGIH TLV	OSHA PEL
CHROMIUM	0.2 MG/M ³ TWA (INHALABLE FRACTION)	1.0 MG/M ³ TWA
NICKEL	0.5 MG/M ³ TWA INHALABLE FRACTION	1.0 MG/M ³ TWA
MANGANESE	0.1 MG/M ³ TWA (INHALABLE) 0.02 MG/M ³ TWA (RESPIRABLE)	5 MG/M ³ CEILING
COBALT	0.02 MG/M ³ TWA	0.1 MG/M ³ TWA (AS METAL DUST AND FUME)

APPROPRIATE ENGINEERING CONTROLS: USE LOCAL EXHAUST OR GENERAL VENTILATION AS REQUIRED TO MINIMIZE EXPOSURE TO DUST AND FUMES; AND TO MAINTAIN THE CONCENTRATION OF CONTAMINANTS BELOW OCCUPATIONAL APPLICABLE LIMITS.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

RESPIRATORY PROTECTION: USE NIOSH APPROVED RESPIRATOR IF EXPOSURE LIMITS ARE EXCEEDED OR WHERE DUST/FUME EXPOSURES ARE EXCESSIVE. SELECTION OF RESPIRATORY PROTECTION DEPENDS ON THE CONTAMINANT TYPE, FORM AND CONCENTRATION. SELECT AND USE RESPIRATORS IN ACCORDANCE WITH OSHA 1910.134 AND GOOD INDUSTRIAL HYGIENE PRACTICE.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION (CONT.)

SKIN PROTECTION: WEAR PROTECTIVE GLOVES. FIRE/FLAME RESISTANT/RETARDANT CLOTHING MAY BE APPROPRIATE DURING HOT WORK WITH THE PRODUCT.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS.

OTHER: PROTECTIVE CLOTHING AS NEEDED TO PREVENT CONTAMINATION OF PERSONAL CLOTHING. THERMAL PROTECTION AS NEEDED WHEN WORKING WITH HEATED MATERIAL.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE (PHYSICAL STATE, COLOR, ETC.): SOLID SILVER-GRAY METALLIC.

ODOR: NO ODOR

ODOR THRESHOLD: N/A	PH: N/A
MELTING POINT/FREEZING POINT: 1371 - 1538 °C / 2500 - 2800 °F	BOILING POINT: N/A
FLASH POINT: N/A	EVAPORATION RATE: N/A
FLAMMABILITY (SOLID, GAS): N/A	
FLAMMABLE LIMITS: LEL: N/A	UEL: N/A
VAPOR PRESSURE: N/A	VAPOR DENSITY: N/A
RELATIVE DENSITY: 7.65 – 7.94	SOLUBILITY(IES): NOT SOLUBLE
PARTITION COEFFICIENT: N-OCTANOL/WATER: N/A	AUTO-IGNITION TEMPERATURE: N/A
DECOMPOSITION TEMPERATURE: N/A	VISCOSITY: N/A

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: NOT NORMALLY REACTIVE.

CHEMICAL STABILITY: STABLE.

POSSIBILITY OF HAZARDOUS REACTIONS: CAN REACT WITH STRONG ACIDS TO FORM HYDROGEN GAS.

CONDITIONS TO AVOID: NONE

INCOMPATIBLE MATERIALS: OXIDIZERS AND STRONG ACIDS.

HAZARDOUS DECOMPOSITION PRODUCTS: AT TEMPERATURES ABOVE THE MELTING POINT, HAZARDOUS FUMES CONTAINING METAL OXIDES AND OTHER ALLOYING ELEMENTS MAY BE LIBERATED TO INCLUDE HEXAVALENT CHROMIUM.

SECTION 11: TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE:

INGESTION: NONE EXPECTED UNDER NORMAL USE CONDITIONS. MAY CAUSE GASTROINTESTINAL EFFECTS IF SWALLOWED.

INHALATION: EXCESSIVE EXPOSURE TO FUMES, GASES OR DUST MAY CAUSE IRRITATION OF NOSE OR THROAT. INHALATION OF DUSTS / FUMES MAY CAUSE AN ALLERGIC RESPIRATORY RESPONSE. INHALATION OF FUMES MAY RESULT IN METAL FUME FEVER (METALLIC TASTE IN MOUTH, DRYNESS AND IRRITATION OF THROAT, CHILLS AND FEVER). CAUSES DAMAGE TO LUNGS THROUGH PROLONGED OR REPEATED INHALATION.

EYE: DUST PARTICLES OR FILINGS MAY CAUSE ABRASIVE INJURY TO THE EYES.

SKIN: MAY CAUSE MECHANICAL IRRITATION OR ABRASIONS. MAY CAUSE AN ALLERGIC SKIN REACTION.

SECTION 11: TOXICOLOGICAL INFORMATION (CONT.)

CHRONIC: LONG-TERM OVEREXPOSURE TO DUST MAY CAUSE LUNG DAMAGE (FIBROSIS) WITH SYMPTOMS OF COUGHING, SHORTNESS OF BREATH AND DIMINISHED BREATHING CAPACITY. CAUSES DAMAGE TO LUNGS THROUGH PROLONGED OR REPEATED INHALATION. CAUSES DAMAGE TO BRAIN AND CNS THROUGH PROLONGED OR REPEATED EXPOSURE. SUSPECTED OF DAMAGING MALE FERTILITY.

CARCINOGENICITY: NICKEL COMPOUNDS ARE CLASSIFIED BY IARC AS 1A CARCINOGENIC TO HUMANS, AND BY THE NTP AS KNOWN TO BE A HUMAN CARCINOGEN. COBALT COMPOUNDS ARE CLASSIFIED BY IARC AS 2B POSSIBLY CARCINOGENIC TO HUMANS. NONE OF THE OTHER COMPONENTS LISTED AT 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR POTENTIAL CARCINOGEN BY OSHA, NTP OR IARC.

NUMERICAL MEASURES OF TOXICITY:

NICKEL: ORAL RAT LD50 > 9000 MG/KG

CHROMIUM: ORAL RAT LD50 > 5000 MG/KG

MANGANESE: ORAL RAT LD50 > 2000 MG/KG, INHALATION RAT LC50 > 5.14 MG/L

COBALT: ORAL RAT LD50 550 MG/KG, DERMAL RAT LD50 > 2000 MG/KG

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY:

NICKEL: 96 HR. LC50 ONCORHYNCHUS MYKISS 15.3 MG/L

MANGANESE: 96 HR. LC50 ONCORHYNCHUS MYKISS LC50 > 3.6 MG/L

PERSISTENCE AND DEGRADABILITY: BIODEGRADATION IS NOT APPLICABLE TO INORGANIC COMPOUNDS.

BIOACCUMULATIVE POTENTIAL: NO DATA AVAILABLE

MOBILITY IN SOIL: NO DATA AVAILABLE

OTHER ADVERSE EFFECTS: NO DATA AVAILABLE

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE/PROVINCIAL AND FEDERAL REGULATIONS. LOCAL REGULATIONS MAY BE MORE STRINGENT THAN REGIONAL AND NATIONAL REQUIREMENTS. IT IS THE RESPONSIBILITY OF THE WASTE GENERATOR TO DETERMINE THE TOXICITY AND PHYSICAL CHARACTERISTICS OF THE MATERIAL TO DETERMINE THE PROPER WASTE IDENTIFICATION AND DISPOSAL IN COMPLIANCE WITH APPLICABLE REGULATIONS.

SECTION 14: TRANSPORT INFORMATION

DOT HAZARDOUS MATERIALS DESCRIPTION: NOT REGULATED

SECTION 15: REGULATORY INFORMATION

SARA SECTION 313: THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372 (TOXIC CHEMICAL RELEASE REPORTING):

CHEMICAL NAME	CAS NO.	WEIGHT-%	SARA 313 - THRESHOLD VALUES %
NICKEL	7440-02-0	1-10	0.1
CHROMIUM	7440-47-3	10-<25	1.0
MANGANESE	7439-96-5	0.1-<2.5	1.0
COBALT	7440-48-4	0.1-1	0.1

SARA 311/312 HAZARD CATEGORIES

ACUTE HEALTH HAZARD	YES
ACUTE HEALTH HAZARD	YES
FIRE HAZARD	NO
SUDDEN RELEASE OF PRESSURE HAZARD	NO
REACTIVE HAZARD	NO

SECTION 15: REGULATORY INFORMATION (CONT.)

CWA (CLEAN WATER ACT)

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES WHICH ARE REGULATED POLLUTANTS PURSUANT TO THE CLEAN WATER ACT (40 CFR 122.21 AND 40 CFR 122.42):

NICKEL CAS# 7440-02-0
CHROMIUM CAS# 7440-47-3

CERCLA

THIS MATERIAL, AS SUPPLIED, CONTAINS ONE OR MORE SUBSTANCES REGULATED AS A HAZARDOUS SUBSTANCE UNDER THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) (40 CFR 302).

CHEMICAL NAME HAZARDOUS SUBSTANCES RQS	CHEMICAL NAME HAZARDOUS SUBSTANCES RQS
NICKEL	100 LBS.
CHROMIUM	5000 LBS.

US STATE REGULATIONS

CALIFORNIA PROPOSITION 65

THIS PRODUCT CONTAINS THE FOLLOWING PROPOSITION 65 CHEMICALS:

CHEMICAL NAME	CALIFORNIA PROPOSITION 65
NICKEL	CARCINOGEN
COBALT METAL POWDER	CARCINOGEN

INTERNATIONAL INVENTORIES

TSCA COMPLIES
 DSL/NDSL COMPLIES
 EINECS/ELINCS COMPLIES
 ENCS COMPLIES
 IECSC COMPLIES
 KECL COMPLIES
 PICCS COMPLIES
 AICS COMPLIES

LEGEND:

TSCA - UNITED STATES TOXIC SUBSTANCES CONTROL ACT SECTION 8(B) INVENTORY
DSL/NDSL - CANADIAN DOMESTIC SUBSTANCES LIST/NON-DOMESTIC SUBSTANCES LIST
EINECS/ELINCS - EUROPEAN INVENTORY OF EXISTING CHEMICAL SUBSTANCES/EUROPEAN LIST OF NOTIFIED CHEMICAL SUBSTANCES
ENCS - JAPAN EXISTING AND NEW CHEMICAL SUBSTANCES
IECSC - CHINA INVENTORY OF EXISTING CHEMICAL SUBSTANCES
KECL - KOREAN EXISTING AND EVALUATED CHEMICAL SUBSTANCES
PICCS - PHILIPPINES INVENTORY OF CHEMICALS AND CHEMICAL SUBSTANCES
AICS - AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES

SECTION 16: ADDITIONAL INFORMATION

ISSUE DATE: 02/11/2024
 SUPERSEDES SDS 11/12/2021